

SCGCTM

Product Name



High Density Polyethylene

Issue date 19 April 2024 (Valid for 1 year)

Product Type

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking		
1.1	Product identifier	
	Trade name: $SCGC^{TM} HDPE$	
	Product type: High Density Polyethylene (HDPE)	
	This SDS applies to all grades of HDPE manufactured by Long Son Petrochemicals Co.,	Ltd.
1.2	Relevant identified uses of the substance or mixture and uses advised against	
	Application of the substance / the preparation: Raw material for different industrial uses	
1.3	Details of the supplier of the safety data sheet	
	Manufacturer/Supplier:	Further information obtainable from:
	Long Son Petrochemicals Co., Ltd.	Central Laboratory Department or Health Safety Security and Environment
	Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Ba Ria	Department
	- Vung Tau, Vietnam	Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Ba
	Tel: +84 254-3514 000	Ria - Vung Tau, Vietnam.
	www.lsp.com/ www.scgchemicals.com	Tel: +84 254-3514-114/ +84 254-3514-115
		or
		Technical Service and Development
		Address: 15th Floor, WORC@Q2, 21 Vo Truong Toan, Thao Dien Ward, Thu Duc
		City, HCM City.
		Tel: +84 2543 514 000 Ext 2401

1.4 Emergency telephone number:

Health Safety Security and Environment Department Tel: +84 254-3514-114/ +84 254-3514-115

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

• Classification according to Globally Harmonized System (GHS):

The substance is not classified as hazardous according to GHS.

• Classification according to Regulation (EC) No 1272/2008 (CLP):

The substance is not classified as hazardous according to the CLP regulation.

• Classification according to Directive 67/548/EEC or Directive 1999/45/EC:

The substance is not classified as hazardous according to Directive 67/548/EEC or Directive 1999/45/EC.

2.2 Label elements

•	Labelling according to GHS:	None
•	Labelling according to Regulation (EC) No 1272/2008:	None
•	Hazard pictograms:	None
•	Signal word:	None

Long Son Petrochemicals Co., Ltd.

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam, Tel. +84 0254-3514 000 Fax: +84 254-3514 001

SCGCTM

LSP

Product Name



High Density Polyethylene

Issue date 19 April 2024 (Valid for 1 year)

• Hazard statements:	None	
Precautionary statements:		
Prevention:	Not Applicable	
Response:	Not Applicable	
Storage:	Not Applicable	
Disposal:	Not Applicable	
Additional information:		
Pellets on the floor may cause a serious slipping hazard.		
Skin or eye contact with hot polymer can cause thermal burns.		
Processing the polymer at high temperatures may form vapors that irritate the eyes and respiratory tract.		
Other hazards		
• Results of PBT and vPvB assessment		
- PBT:	Not determined	

- vPvB:

SECTION 3:

2.3

Composition/information on ingredients

3.1 Chemical characterization:	Mixture		
Chemical Name	CAS No.	EC No.	Concentration (wt%)
Polyethylene Homopolymer or			> 99%
Ethylene-1 butene copolymer	9002-88-4 or 25087-34-7	-	~ 9970
Additives	-	-	< 1%

Not determined

SECTION 4: First Aid Mea

4.1 Description of first aid measures:

• General information:

Take affected persons out of danger area and lay down.

• After inhalation:

Move person to fresh air; if symptoms persist, consult a doctor.

• After skin contact:

Wash exposed area with soap and water. Seek medical attention if symptoms develop or persist. If molten polymer comes in contact with the skin, cool rapidly with cold water or running water. Do not pull solidified polymer off the skin. Seek medical attention immediately.

• After eye contact:

In case of dust contact with eyes, flush thoroughly with running water for 5-15 minutes. Remove contact lenses, if worn. Seek medical attention if irritating persists. For thermal eye burns, immediately flush eyes with running water for 5-15 minutes. Do not remove contact lenses, if worn. Seek medical attention immediately, preferably an ophthalmologist.

After swallowing:

Rinse out mouth with water and gargle with plenty of water. If swallowed, consult a doctor. May cause gastrointestinal blockage. Do not give laxative. Do not induce vomiting unless directed to do so by medical personnel.

Long Son Petrochemicals Co., Ltd.

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam. Tel. +84 0254-3514 000 Fax: +84 254-3514 001

Product Name

SCGCTM



High Density Polyethylene

LSP

High Density Polyethylen

Issue date 19 April 2024 (Valid for 1 year)

Product Type

4.2 Most important symptoms and effects, both acute and delayed:

Skin and eye burns from molten product. Skin and eye irritation from product dusts. Irritated respiratory tract from dust inhalation.

4.3 Indication of any immediate medical attention and special treatment needed:

Treat symptomatically and supportively.

SECTION 5: Firefighting Measures

5.1 Extinguishing media:

• Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

Use fire extinguishing methods suitable to surrounding conditions.

• Unsuitable extinguishing agents:

Do not use water jet

5.2 Special hazards arising from the substance or mixture:

• Hazard combustion products:

Carbon dioxide (CO₂), Carbon monoxide (CO), other organic vapors and soot.

5.3 Advice for firefighters:

• Protective equipment:

Fire-fighters should wear appropriate protective equipment (includes fire-fighting helmet, coat, trousers, boots and gloves) and positive pressure self-contained breathing apparatus (SCBA).

• Fire Fighting Procedure:

Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream.

Use fine water spray or foam. Cool surroundings with water to localize fire zone.

Additional information:

Collect contaminated firefighting water separately. It must not enter the sewage system. Cool endangered receptacles with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

• For non-emergency personnel:

Material creates a slipping hazard on hard surfaces. Clean up spills from walking surfaces immediately. Eliminate sources of ignition. Avoid formation of dust.

• For emergency responders:

Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

6.2 Environmental precautions:

· Avoid dispersal and contact with soil, waterways, sewers and groundwater.

6.3 Methods and material for containment and cleaning up:

- For containment: place in a designated and labeled waste container.
- For cleaning up: sweep or shovel into suitable containers. Do not allow water contaminated with pellets
- or powder to enter any waterway, sewer or drain.
- Other information: Dispose of contaminated material at an authorized site. Notify authorities if product enters sewers or public waters.

Long Son Petrochemicals Co., Ltd.

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam. Tel. +84 0254-3514 000 Fax: +84 254-3514 001



High Density Polyethylene

Product Name

SCGCTM



Issue date 19 April 2024 (Valid for 1 year)

Product Type

6.4 Reference to other sections:

- · See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling:

Protective Measures:

Put on appropriate personal protective equipment (see Section 8). Avoid contacting molten material with eyes, skin and clothing. Avoid breathing dust and process fumes. Ensure good ventilation at the workplace. Prevent dust accumulation. Pneumatic conveying of powder and pellets and other mechanical handling operations can generate large static electrical charges. Dust can be ignited by static electrical discharge. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Worker should handle the container with appropriate apparatus such as forklift and handlift. If worker feel stiff, should take a rest sufficiently.

Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Always wash hands after handling the product.

7.2 Conditions for safe storage, including any incompatibilities:

Technical measures and storage conditions:

Electrically bond and ground equipment to reduce the potential for dust explosions. Store in dry, cool, dust-free and well-ventilated area at temperature below 50°C. Protect from heat, direct sunlight and rain.

Packaging materials:

Store only in the original container. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

· Materials to avoid:

Store away from incompatible substances, flammable substances and oxidizing agents.

• Further information about storage conditions:

Use an appropriate handling and storage method as described in Manufacturer's "Handling and storage guide" Manual. (Please visit this website www.scgchemicals.com)

7.3 Specific end uses:

No further relevant information available.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters:

Occupational Exposure Limits

8.2.1 Appropriate engineering controls:

8.2 Exposure controls:

Not established

•

Provide readily accessible eye wash stations and safety showers. Ensure adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation

Long Son Petrochemicals Co., Ltd.

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam. Tel. +84 0254-3514 000 Fax: +84 254-3514 001 Page |4



Product Name



8.2.2 Personal protective equipment:

• Eye/Face protection

Skin protection
 Hand protection

- Body protection

Respiratory protection

8.2.3 Environmental exposure control:

High Density Polyethylene

Issue date 19 April 2024 (Valid for 1 year)

Product Type

or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

LSF

Use safety glasses with side shields. If this material is heated and there is potential for dust, wear chemical goggles.

Skin contact should be minimized. Use gloves to protect from mechanical injury. Chemical protective gloves should not be needed when handling this material. Use insulated gloves when handling the hot or molten material.

At ambient temperatures use of clean and protective clothing is good industrial practice. If the material is heated or molten, wear thermally insulated, heat-resistant gloves that are able to withstand the temperature of the molten product. If this material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate.

A properly fitted air purifying respirator or air supply.

respirator should be worn if a risk assessment indicates that respiratory protection is necessary. Respirator selection must be based upon known or measured levels of exposure.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9:

9.1

Physical and chemical properties

1	Information on basic physical and chemical properties:	
	• Appearance:	Pellets
	Physical state:	Solid
	• Color:	Clear to opaque, whitish
	• Odor:	Light
	• Odor threshold:	No data available
	• pH:	Not applicable
	• Melting point:	125-135 ℃
	Boiling point:	Not applicable
	• Flash point:	No data available
	• Evaporation rate:	Not applicable
	• Flammability (solid, gas):	No
	• Upper/lower explosion limits:	Not applicable
	• Vapor pressure:	Not applicable
	• Vapor density	Not applicable
	• Relative density:	No data available

Long Son Petrochemicals Co., Ltd.

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam. Tel. +84 0254-3514 000 Fax: +84 254-3514 001

SCGCTM

Product Name



High Density Polyethylene

LSP

Issue date 19 April 2024 (Valid for 1 year)

Product Type

• Density at 23 [°] C	0.94-0.97 g/cm ³
• Solubility in water:	Insoluble.
• Partition coefficient, n-octane/water:	No data available
• Auto-ignition temperature:	No data available
Decomposed temperature:	No data available
• Viscosity, kinematic:	Not applicable
• Viscosity, dynamic:	No data available
• Explosive properties:	No
Oxidizing properties:	No
Other information:	No further relevant information available.

SECTION 10: Stability and Reactivity

10.1 Reactivity:

9.2

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:

The product is stable at normal handling and storage conditions.

10.3 Possibility of hazardous reactions:

Polymerization will not occur. Dust may form explosive mixture in air.

10.4 Conditions to avoid:

Avoid prolonged storage at elevated temperature. Exposure to elevated temperatures can cause product to decompose (Temperature should less than 300°C). See Technical

Datasheet for suitable processing condition.

Avoid dust formation.

Avoid the build-up of electrostatic charge.

10.5 Incompatible materials:

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products:

Burning can produce carbon monoxide and/or carbon dioxide and other harmful products. The decomposition products are low molecular weight oligomers, hydrocarbons and hydrocarbon oxidation product (aldehydes, alcohols, organic acids) depending on temperature and air availability.

SECTION 11: Toxicological Informati

- Acute toxicity:
 - LD50 oral, rat
- Skin corrosion/irritation:

Not determined. Non-irritating to skin. Mechanical injury only. Molten

polymer may cause serious thermal burns.

Long Son Petrochemicals Co., Ltd.

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam. Tel. +84 0254-3514 000 Fax: +84 254-3514 001 P a g e |6

SCGCTM

LSP

Product Name



High Density Polyethylene

Issue date 19 April 2024 (Valid for 1 year)

Product Type

• Eye damage/irritation:	Dust may cause eye irritation upon repetitive or prolonged exposure. Molten
	polymer may cause serious thermal burns. Vapors released during thermal
	processing may cause eye irritation experienced as mild discomfort and redness.
• Sensitization to the respiratory tract:	No effects are expected for ingestion of small amounts.
	May cause choking if swallowed.
Skin sensitization:	No relevant data found.
Germ cell mutagenicity:	No relevant data found.
Carcinogenicity:	No relevant data found.
Reproductive toxicity:	No relevant data found.
Additional toxicological information:	When used and handled according to specifications, the
	product does not have any harmful effects to our experience and the information provided to us.

SECTION 12: Ecological Information

12.1 Toxicity:

	• Aquatic toxicity:	Not expected to be acutely toxic, but material in pellet
		form may mechanically cause adverse effects if ingested by waterfowl or aquatic life.
12.2	Persistence and degradability:	Not easily biodegradable
12.3	Bioaccumulative potential:	This material is not expected to bioaccumulation because
		of the relatively high molecular weight (MW greater than 1000).
12.4	Mobility in soil:	This material is expected to remain in the soil and float on the water surface
12.5	Results of PBT and vPvB assessment:	
	• PBT:	Not determined
	• vPvB:	Not determined
12.6	Other adverse effects:	Avoid release to the environment.

SECTION 13:

Disposal Considerations

- 13.1 Waste treatment methods:
 - Waste disposal: Do not dump into any sewers, on the ground, or into any body of water. All disposal practices must be in compliance with official or local regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable regulations are the responsibility solely of the waste generator.
 Packaging disposal: Do not reuse container. Disposal must be in compliance with applicable with official or local regulations. The packaging only use for industrial purpose.
 Waste treatment option: Recycle if possible
 Other disposal recommendations : Disposal must be made according to official or local regulations.

Long Son Petrochemicals Co., Ltd.

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam, Tel. +84 0254-3514 000 Fax: +84 254-3514 001 Page |7



SCGCTM

Product Name

LSP

High Density Polyethylene

Issue date 19 April 2024 (Valid for 1 year)

Product Type

SECTION 14: Transport information

14.1 Land transport (ADR/RID)

- UN-Number:
- UN proper shipping name:
- Transport hazard class(es):
- Packing group:
- 14.2 Inland waterways transport (ADN)
 - UN number:
 - UN proper shipping name:
 - Transport hazard class(es):
 - Packing group:

14.3 Marine transport (IMDG)

- UN number:
- UN proper shipping name:
- Transport hazard class(es):
- Packing group:

14.4 Air transport (ICAO-TI/IATA-DGR)

- UN number:
- UN proper shipping name:
- Transport hazard class(es):
- Packing group:
- 14.5 Environmental hazards:

ENVIRONMENTALLY HAZARDOUS:

- 14.6 Special precautions for user:
- 14.7 Transport in bulk:

(According to Annex II of MARPOL73/78 and the IBC Code)

- Transport/Additional information:
- UN "Model Regulation":

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No

Not applicable.

Not applicable.

Not dangerous according to the above specifications.

SECTION 15:

Regulatory information

Other information

- 15.1 Chemical inventories
- 15.2 Chemical safety assessment:

More information on Declaration of Compliance (DoC) A Chemical Safety Assessment has not been carried out.

Recommended Uses and Restrictions

This product is a raw material for industrial conversion. We recommended you to use this product under description in this document only.

Long Son Petrochemicals Co., Ltd.

SECTION 16:

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam. Tel. +84 0254-3514 000 Fax: +84 254-3514 001

LSP and SCG Internal

Page | 8



SCGCTM

Product Name



High Density Polyethylene

Issue date 19 April 2024 (Valid for 1 year)

Issued by

Long Son Petrochemicals Company Limited (Central Laboratory Department)

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Ba Ria - Vung Tau, Vietnam.

Product Type

Tel. +84 254-3514 000

Fax: +84 254-3514 001

Disclaimer:

- It is customer's responsibilities to inspect and test the product for suitability of the customer's own use and purpose. The customer is responsible for appropriate, safe, legal use, processing and handling of the product.
- To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication. We however do not assume any liability whatsoever for the accuracy and completeness of the information contained herein.
- We make no warranties which extend beyond the description herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose.
- No liability can be accepted in respect of the use of the product in conjunction with other materials. The information contained herein relates exclusively to the product when it is not used in conjunction with any third party's materials.

Abbreviations and acronyms:

- ADR : Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning
- The International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LD50: Lethal Dose 50% kill

Long Son Petrochemicals Co., Ltd.

Hamlet 2, Long Son Commune, Vung Tau City, Ba Ria - Vung Tau Province, Vietnam Ba Ria - Vung Tau – Vietnam, Tel. +84 0254-3514 000 Fax: +84 254-3514 001